TC Installations Limited
Units 11 – 13 Highlode Industrial Estate, Stocking Fen Road Ramsey, Cambridgeshire. PE26 2RB

Tele: +44 (0) 1487 710555
FAX +44 (0) 1487 710060

Power Over LAN.

TCPOE101

Single Port

TCPOE106

6 Port requires Rack Mount (TCRCK101)

TCPOE106-N
TCPOE112-N

6/12/24 Port 19 inch Rack Mountable

TC Installations offer Midspan POE devices that are IEEE 802.3af compliant.

Specification

No. of Ports 1/6/12/24

Pass Through Data Rates	10/100 Mbps
Power over Ethernet	Pin Assignment and Polarity:
Output	4/5 (+), 7/8 (–)
Output Power	Voltage: 48Vdc
User Port Power:	15.4Watts Max.
Aggregate Power:	up to 200Watts
Input Power	AC Input Voltage: 90 - 264
Requirements	AC Input Current: 4A @ 110 2A @ 240
AC Frequency:	50 to 60 Hz
Dimensions 12/24 Port	438mm x 272mm x 44mm 17.3 in. x 17.7 in. x 1.73 in
Weight	8.8 lbs (4 kg)
Dimensions 6 Port	281mm x 284mm 44mm 11.06 in. x 11.18 in x 1.73 in.
Weight	2.4 lbs (1.1 kg)

Indicators

System Indicator:	AC Power (Green)
User Indicator:	Channel Power (Green)
Connectors Shielded	RJ-45, EIA 568A and 568B

Environmental Operating Ambient Temperature:

Conditions	0 to 40ºC
Operating Humidity:	Max 90%, Non-condensing
Storage Temperature:	20º to 70ºC
Storage Humidity:	Max 95%, Non-condensing
Operating Altitude:	–1000 to 10,000 ft. (–304.8 to 3048 m)
Reliability MTBF:	100,000 hrs. @25ºC
Thermal Rating	300 BTU/Hr (@240VAC)
Warranty	1-year
Regulatory	IEEE 802.3af (PoE), RoHS Compliant
Compliance	WEEE Compliant, CE
Electromagnetic	Cabling FCC Part 15, Class B with FTP
Emission & Immunity	EN 55022 Class B (Emissions) EN55024 (Immunity), VCCI
Safety Approvals	UL/cUL Per EN 60950 GS Mark Per EN 60950

Ordering.

Part No:	Single Port	TCPOE101
	6 Port	TCPOE106-N
	6 Port 1G	TCPOE106-G
	12 Port	TCPOE112-N
	24 Port	TCPOE124